

### FITTING INSTRUCTIONS FOR EH0044BK EXHAUST HANGER YAMAHA FZ8 2010

Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike

- Remove the original rear footpegs/exhaust hanger.
- Place the two M8 button head bolts from kit through the two top holes in the R&G hanger.
- Offer up to bike as shown above and engage threads (do not tighten yet).
- Place the M10 button head bolt from kit through the exhaust mounting hole (lower hole in bracket).
- Place the rubber gasket over exposed end of bolt (so it sits between hanger and exhaust mounting bracket).
- Engage the thread into the captive exhaust mounting nut.
- Tighten all bolts evenly.
- Please ensure when the motorcycle is being used that no parts are in such a position that they may collide/damage other bike parts (this is particularly important if using after-market cans or exhaust systems).

Please note that it is your responsibility to ensure that no part of the exhaust hanger or exhaust assembly fouls or comes into contact with other parts of the machine. Do not ride the motorcycle until this aspect has been verified and you have compressed the rear suspension (if appropriate to the design of the motorcycle) to test this thoroughly.

#### CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

#### **R&G RACING RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in resellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.



# FRANCE INSTRUCTIONS DE MONTAGE EH0044BK YAMAHA FZ8 2010

Notez s'il vous plaît que la façon dont le kit est empaqueté ne représente pas nécessairement la façon de montage sur la moto.

- Enlever le support d'échappement / repose pied arrière d'origine.
- Placer deux vis M8 (fournies dans le kit) à travers les deux trous (les plus en haut) sur le nouveau support R&G.
- Placer le tout sur la moto et engager à la main les vis (ne pas serrer pour le moment).
- Placer la vis M10 (fournie dans le kit) à travers le trou sur le nouveau support R&G. (trou de fixation positionné en bas du support de pot).
- Placer le joint en caoutchouc sur le filetage de la vis précédemment installée. (cette pièce sera donc placée entre le support R&G et la patte de fixation du silencieux).
- Engager ensuite la vis M10 dans le filetage de l'écrou situé sur le silencieux.
- Serrer les 3 vis.
- Assurez qu'aucune pièce ne puisse être en contact/collision avec les autres pièces de la moto. (Particulièrement important lorsque le silencieux et autres accessoires sont des pièces adaptables).

Notez s'il vous plaît que c'est votre responsabilité d'assurer qu'aucune partie du support d'échappement ou de l'échappement ne puisse entrer en contact avec d'autres parties de la machine. Ne roulez pas avec le véhicule avant d'avoir vérifier le bon montage de la pièce (compresser la suspension arrière pour vérifier la qualité du montage).




## FITTING INSTRUCTIONS FOR BLP0005BK REAR FOOTREST BLANKING PLATE YAMAHA FZ8 2010 RIGHT AND LEFT HAND SIDES



### THIS KIT CONTAINS THE ITEMS PICTURED AND LABELLED BELOW. DO NOT PROCEED UNTIL YOU ARE SURE ALL PARTS ARE PRESENT.

Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike

THE PARTS SHOWN MAY BE REPRESENTATIVE ONLY (FOR CLARITY OF INSTRUCTIONS ONLY)





Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – the rubber washers should be thrown away!

### TOOLS REQUIRED

• Set of metric Allen keys to include 5 and 6mm A/F sizes.

### FITTING INSTRUCTIONS

- Using 6mm allen key remove the two bolts and remove rear footrest.
- Fit two of the button headed bolts through the blanking plate.
- Offer assembly up to bike and engage both bolts
- Tighten evenly using 5mm Allen key.

### CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

### **R&G RACING RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in resellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com