




FITTING INSTRUCTIONS FOR TP0018BK FOOTBOARD SLIDERS
YAMAHA X-MAX 400 2013-



THIS KIT CONTAINS THE ITEMS PICTURED AND LABELLED BELOW.
DO NOT PROCEED UNTIL YOU ARE SURE ALL PARTS ARE PRESENT.

Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike.

THE PARTS SHOWN MAY BE REPRESENTATIVE ONLY (FOR CLARITY OF INSTRUCTIONS ONLY)



R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



LEGEND

- ITEM 1 = SLIDER (SL0007) (x2).
- ITEM 2 = MOUNTING PLATE LEFT SIDE (MP0081) (x1).
- ITEM 3 = M6x30mm LONG COUNTERSUNK BOLTS (x2).
- ITEM 4 = SPACER (S0704) 19mm LONG (x2).
- ITEM 5 = SPACER (S0705) 16mm LONG (x2).
- ITEM 6 = 10.5mm PUNCH TOOL (x1).
- ITEM 7 = M6 MARKING TOOL (x1).
- ITEM 8 = MOUNTING PLATE RIGHT SIDE (MP0082) (x1).
- ITEM 9 = M5x12mm LONG COUNTERSUNK BOLTS (x6).

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – *the rubber washers should be thrown away!*

TOOLS REQUIRED

- Set of metric Allen keys to include 3 & 4mm A/F sizes.
 - 10mm Socket and wrench.
 - Hammer/mallet.



PICTURE 1



PICTURE 2




PICTURE 3



PICTURE 4



PICTURE 5



PICTURE 6

FITTING INSTRUCTIONS

- To fit the left side, remove the original rubber foot plate by lifting a corner and gently pulling.
- Remove the two 10mm bolts that are now accessible, as arrowed in picture 1.
- Take the M6 making tool (item 8) that is in the kit and screw into one of these holes, ensuring the point is at the top, as shown in picture 2. Re-fit the original rubber foot plate and gently apply some pressure to the area around the marking tool. *This should give a small indentation to locate where to punch a hole through the rubber in order to fit the bolt.* Use the same process to locate the other bolt hole.
- With the rubber removed from the scooter, use the 10.5mm Punch Tool (item 7) supplied with the kit along with a hammer/mallet to create two holes where there is a mark, as shown in picture 3. *This should be done with a scrap piece of wood underneath the rubber and on a hard surface.*
- These holes then allow the top of the spacers to fit through in order for the bolt to tighten against, as shown in picture 4.
- Take the left side mounting plate (item 2) and fit the slider (item 1) using three of the M5 countersunk bolts (item 9). Fit the bolts through the slider and screw into the mounting plate and tighten, as shown in picture 5.
- On the scooter, position the 19mm long spacer (item 4) in the front recess (with the stepped down smaller diameter facing upwards) and the 16mm long spacer (item 5) on the rear mount (again, with the stepped down smaller diameter facing upwards), as arrowed in picture 6.
- Re-fit the original foot plate rubber, ensuring that the tops of the two spacers fit through the holes that have just been punched in the rubber.
- Offer the R&G footboard slider assembly into position and insert the M6 x 30mm long countersunk bolts (item 3) through the mounting plate and into the spacer, sandwiching the rubber, before tightening evenly.
- Place the reflective bubble stickers into recesses to cover the bolt heads.
- To fit the right side, follow the same procedure as above.

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.




Instructions de montage pour TP0018BK Sliders de marche pied
YAMAHA X-MAX 400 2013-



LE KIT CONTIENT LES ARTICLES EXPOSES CI-DESSOUS, VERIFIER QUE TOUTES LES PIECES SOIENT PRESENTES AVANT DE PROCEDER AU MONTAGE.

LA FAÇON DONT LE KIT EST EMBALLE NE CORRESPOND PAS FORCLEMENT A LA FAÇON DE MONTER LES PIECES SUR LA MOTO.

LES PARTIES PRESENTEES PEUVENT ETRE UNIQUEMENT REPRESENTATIVES (POUR LA CLARTE DES INSTRUCTIONS UNIQUEMENT)





COTÉ GAUCHE

9

COTÉ DROIT

9

LEGENDE

- ARTICLE 1 = SLIDER (SL0007) (x2).
- ARTICLE 2 = PLAQUE DE MONTAGE COTE GAUCHE (MP0081) (x1).
- ARTICLE 3 = BOULONS M6x30mm (x2).
- ARTICLE 4 = ENTRETOISE (S0704) 19mm de long (x2).
- ARTICLE 5 = ENTRETOISE (S0705) 16mm de long (x2).
- ARTICLE 6 = 10.5mm OUTIL DE PERCAGE (x1).
- ARTICLE 7 = M6 OUTIL DE MARQUAGE (x1).
- ARTICLE 8 = PLAQUE DE MONTAGE COTE DROIT (MP0082) (x1).
- ARTICLE 9 = M5x12mm BOULONS (x6).

Notez que si les kits sont emballés avec des rondelles en caoutchouc servant à tenir les composants, *ces rondelles doivent être jetées.*

OUTILS REQUIS

- Jeu de clés Allen 3 et 4mm.
 - Clé 10mm.
 - Maillet.



PHOTO 1



PHOTO 2



R&G Racing



PHOTO 3

PHOTO 4



PHOTO 5




PHOTO 6

INSTRUCTIONS DE MONTAGE :

- Pour l'installation du coté gauche de la moto, retirer la plaque de pied en caoutchouc d'origine en soulevant un coin et en tirant doucement.
- Enlever les 2 boulons 10mm qui sont à présent accessibles (Photo 1).
- Prendre l'outil de marquage M6 (Article 8) présent dans le kit et vissez-le dans un des trous, en veillant à ce que le point soit vers le haut (Photo 2). Remettre la plaque de pied en caoutchouc d'origine et appliquez une légère pression sur l'endroit qui entoure l'outil de marquage. Cela devrait donner un léger renforcement qui sert à identifier l'endroit où percer le trou dans le caoutchouc pour passer le boulon. Utiliser le même processus pour placer l'autre trou de boulon.
- Une fois le caoutchouc enlevé du scooter, utiliser l'outil de pousse 10.5mm (Article 7) fourni dans le kit avec un maillet pour créer 2 trous, là où se trouvent les marques (Photo 3). Cela peut s'effectuer avec un petit morceau de bois sous le caoutchouc et sur une surface rigide.
- Ces trous permettent aux entretoises de passer à travers pour que le boulon soit serré contre elle (Photo 4).
- Prendre la plaque de montage coté gauche (Article 2) et installez le slider (Article 1) en utilisant 3 des boulons M5 (Article 9). Monter les boulons à travers le slider et vissez-les dans la plaque de montage puis serrez (Photo 5).
- Sur le scooter, positionnez l'entretoise 19mm (Article 4) dans le creux avant (avec le plus petit diamètre vers le haut) et l'entretoise 16mm (Article 5) sur le support arrière (une nouvelle fois, avec le plus petit diamètre vers le haut), (Photo 6).
- Remettre la plaque de pied en caoutchouc d'origine, en veillant à que le haut des 2 entretoises passent à travers les trous qui viennent juste d'être créés dans le caoutchouc.



- Mettre le slider de marche pied en position et insérez les boulons M6 x 30mm (Article 3) à travers la plaque de montage et dans l'entretoise, prenant en sandwich le caoutchouc, avant de serrer de façon égale.
- Placer les stickers en caoutchouc dans les creux pour couvrir les têtes des boulons.
- Pour l'installation du coté droit, suivez le même processus.

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.