

FITTING INSTRUCTIONS FOR FP0146BK FORK PROTECTORS HONDA CBR650F 2013




THIS KIT CONTAINS THE ITEMS PICTURED AND LABELLED BELOW. DO NOT PROCEED UNTIL YOU ARE SURE ALL PARTS ARE PRESENT.

Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike

Please note that in cases where kits are packed with a plastic tube separating components on the spindle bar (this tube should be discarded).

THE PARTS SHOWN MAY BE REPRESENTATIVE ONLY (FOR CLARITY OF INSTRUCTIONS ONLY)



Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



TOOLS REQUIRED

• Socket set to include 2x 13mm sockets, 22mm socket and wrenches

FITTING INSTRUCTIONS

- Remove the axle bolt from the right hand side fork leg using a 22mm socket.
- Replace this bolt with the bolt supplied in the R&G kit and tighten to the recommended torque setting.
- Fit one nut and washer on spindle-bar (SB0106), engage the nut so the plastic insert of nut is fully
 engaged.
- Feed spindle-bar with nut and washer through either crash protector (B0445M) and through the metal spacer (S0715) with the larger diameter fitting inside the crash protector.
- Place this assembly through the front wheel spindle from the left hand side.
- Place the remaining crash protector over the exposed end of the spindle bar.
- Fit washer and nut from kit onto thread and tighten until both nuts are engaged in nylon and equal amounts protrude from either side (please ensure the logo is located at the top of the crash protector). Do not overtighten the nyloc nuts will hold it tight.

ISSUE 1 02/09/2013 (NSY)

CONSUMER NOTICE


The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in resellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.



Instructions de montage
FOR FP0146BK Protections fourche
HONDA CBR650F 2013




<u>Vérifier le contenu de la boite avant de déballer les pièces.</u> Ne pas procéder au montage s'en s'être assuré au préalable que les articles soient bien présents.

La façon dont le kit est emballé ne représente pas nécessairement la façon de le monter sur la moto.

Les parties représentées peuvent parfois être uniquement représentatives

(Pour la clarté des explications).

Au cas oû le kit serait fourni avec un tube en plastique séparant les composants sur l'axe (ce tube doit être enlevé).



Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



Outils requis

• Jeu de clefs de 13mm x 2 , Clef de 22mm

Instructions de montage

- Enlever le boulon d'axe du pied de fourche du coté droit avec une clef de 22mm.
- Remplacer ce boulon avec le boulon fourni dans le kit R&G puis serrer au couple recommandé.
- Installer un écrou et une rondelle sur l'axe (SB0106) (L'extrémité avec le filetage le plus court), engager l'écrou de sorte à ce que l'insert en plastique de l'écrou soit complètement engagé.
- Installer l'axe avec écrou et rondelle à travers l'une des 2 protections crash (B0445M) et à travers l'entretoise en métal (S0715) avec le diamètre le plus large en l'installant à travers la protection crash.
- Placer l'ensemble à travers l'axe de roué avant du coté gauche.
- Placer la protection restante autour de l'extrémité opposée de l'axe.
- Installer la rondelle et l'écrou du kit sur le filetage puis serrer jusqu'à ce que les 2 écrous soient engagés dans le nylon et dépassent de chaque coté de la même longueur (s'assurer que le logo soit logé en haut de la protection). Ne pas bloquer les écrous en nyloc bloquent suffisamment.

ISSUE 2 02/09/2013 (NSY)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in resellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.