




FITTING INSTRUCTIONS FOR RAD0367PRO



THIS KIT CONTAINS THE ITEMS PICTURED AND LABELLED OVER PAGE.
SOME PARTS MAY BE SHOWN FOR CLARITY OF INSTRUCTIONS ONLY.

DO NOT PROCEED UNTIL YOU ARE SURE ALL PARTS ARE PRESENT.

PLEASE READ ALL INSTRUCTIONS BEFORE PROCEEDING.

**IF IN ANY DOUBT WHEN FITTING OUR PRODUCTS, CONSULT ONE OF OUR DEALERS
OR HAVE FITTED BY A QUALIFIED TECHNICIAN.**

PLEASE NOTE THAT THE WAY THE KIT IS PACKED DOES NOT NECESSARILY REPRESENT THE WAY OF
MOUNTING TO THE BIKE.

IN THE EVENT OF RUBBER WASHERS BEING USED TO HOLD COMPONENTS ONTO BOLTS,
THESE RUBBER WASHERS CAN BE THROWN AWAY.




<u>TOOLS REQUIRED</u>	<u>GENERAL TORQUE SETTINGS</u>
SET OF ALLEN KEYS	M4 BOLT = 8Nm M5 BOLT = 12Nm M6 BOLT = 15Nm M8 BOLT = 20Nm M10 BOLT = 40Nm M12 BOLT = 40Nm

LEGEND

ITEM NO.	DESCRIPTION	QTY
ITEM 1	RAD0367PRO RADIATOR GUARD	1
ITEM 2	RUBBER BUNG	7


FITTING DIAGRAM

FRONT OF RAD GUARD






FITTING PICTURES:




Picture 1



Picture 2



Picture 3



Picture 4

FITTING INSTRUCTIONS

Assembly:

- Firstly, remove the original radiator guard. This can be done via the two screws and one pop clip on either side of the inner cowlings. (Circled in **Picture 3**)
- Followed by the two upper mounting bolts, then the two lower mounting bolts. (Circled in **Picture 4**)
- Carefully remove the original guard taking extra care not to come into contact with the fins of the radiator while manoeuvring it out from behind the cowls.
- Clean any debris of the radiator, being careful not to damage any of the fins while doing so.
- Prepare the radiator guard by inserting the 5x rubber bungs (**Item 2**) into the radiator guard. (**Picture 1**)

Please note: Fitting the bungs is much easier with the use of a 3mm allen/hex key as shown in

Racing Technique Ltd T/A R&G

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



Picture 2, place the bungs on the end of the allen key and carefully push through the holes.

- Carefully offer the R&G guard up to the radiator, slotting the bottom edge down and behind the tabs circled in green in **Picture 4**.
- Hold the guard back onto the radiator until it sits flush up against the top mounts.
- Loosely thread in the two original upper mounting bolts you removed earlier until the guard is held in place.
- Fully tighten the mounting bolts, then re-fit all original bolts/screws and clips to their original positions.

ISSUE 1 – 04/08/2025 (TB)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.



NOTICE DE MONTAGE POUR RAD0367PRO



CE KIT CONTIENT LES ARTICLES ILLUSTRÉS ET ÉTIQUETES SUR LA PAGE.

CERTAINES PARTIES PEUVENT ÊTRE PRÉSENTES UNIQUEMENT POUR LA CLARTÉ DES INSTRUCTIONS.

NE PAS PROCÉDER AU MONTAGE TANT QUE VOUS N'ÊTES PAS SÛR QUE TOUTES LES PIÈCES SOIENT PRÉSENTES.

VEUILLEZ LIRE TOUTES LES INSTRUCTIONS AVANT DE CONTINUER.

**EN CAS DE DOUTE LORS DU MONTAGE DE NOS PRODUITS, CONSULTEZ UN DE NOS
REVENDEURS OU FAITES APPEL À UN TECHNICIEN QUALIFIÉ.**

VEUILLEZ NOTER QUE LA FAÇON DONT LE KIT EST EMBALLÉ NE REPRÉSENTE PAS NECESSAIREMENT LA MANIÈRE DE
LE MONTER SUR LA MOTO.

SI DES RONDELLES EN CAOUTCHOUC SONT UTILISÉES POUR MAINTENIR LES COMPOSANTS SUR LES BOULONS, ELLES PEUVENT ÊTRE JETÉES.

NOTICE DISPONIBLE AU TÉLÉCHARGEMENT SUR :

WWW.RG-RACING.COM




<u>OUTILS REQUIS</u>	<u>VALEURS DE SERRAGE</u>
CLÉS ALLEN	M4 BOULON = 8Nm M5 BOULON = 12Nm M6 BOULON = 15Nm M8 BOULON = 20Nm M10 BOULON = 40Nm M12 BOULON = 40Nm

LÉGENDE

ARTICLE NO.	DESCRIPTION	QTÉ
ARTICLE 1	RAD0367PRO PROTECTION RADIATEUR	1
ARTICLE 2	BOUCHON EN CAOUTCHOUC	7

SCHÉMA DE MONTAGE

AVANT DE LA PROTECTION RADIATEUR





PHOTOS DE MONTAGE :




Photo 1





Photo 2



Photo 3

**Photo 4**

NOTICE DE MONTAGE

Assemblage :

- Commencez par retirer la protection radiateur d'origine. Pour ce faire, utilisez les deux vis et le clip de chaque côté des capots intérieurs (entourés sur la photo 3).
- Ensuite, retirez les deux boulons de fixation supérieurs, puis les deux boulons de fixation inférieurs (entourés sur la photo 4).
- Retirez délicatement la protection d'origine en veillant à ne pas toucher les ailettes du radiateur lors de sa sortie par l'arrière des capots.
- Nettoyez le radiateur de tous les débris, en veillant à ne pas endommager les ailettes.
- Préparez la protection radiateur en insérant les 5 bouchons en caoutchouc (article 2) dans la protection radiateur (photo 1).

Note : Le montage des bouchons est beaucoup plus facile avec l'utilisation d'une clé

Racing Technique Ltd T/A R&G

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



Allen/hexagonale de 3mm comme indiqué sur l'image 2, placez les bouchons à l'extrémité de la clé Allen et poussez soigneusement à travers les trous.

- Présentez délicatement la protection R&G sur le radiateur, en insérant le bord inférieur vers le bas et derrière les languettes entourées en vert sur la photo 4.
- Maintenez la protection sur le radiateur jusqu'à ce qu'elle soit bien en appui contre les supports supérieurs.
- Vissez sans serrer les deux boulons de fixation supérieurs d'origine retirés précédemment jusqu'à ce que la protection soit maintenue en place.
- Serrez à fond les boulons de fixation, puis remettez tous les boulons/vis et clips d'origine à leur emplacement d'origine.

ISSUE 1 – 04/08/2025 (TB)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty good.