



FITTING INSTRUCTIONS FOR LP0049BK TAIL-TIDY BMW G650 X CHALLENGE, COUNTRY & MOTO 2007



Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – *the rubber washers should be thrown away!*

MOTO and CHALLENGE VERSIONS

- Remove seat.
- Remove rear cowling.
- Unplug OEM No plate and indicator wiring plug.
- Remove OEM tail-tidy (four screws underneath positioned horizontally and quick release pull cable under seat).
- Remove the two screws securing the under-tray to rear sub frame (positioned vertically under OEM tail-tidy).
- Fit OEM indicators (will need to cut loom) or r&g after market indicators (as pictured above) to new tail-tidy.
- Fit new No plate light as pictured above.
- Offer up new tail-tidy as above and secure using short button head screws and washers as shown and washers and nyloc nuts supplied in kit.
- Position the two long spacers between front most holes in new tail-tidy and under-tray, on MOTO and CHALLENGE versions fit the two M5 x 70mm long bolts with washers up through tail-tidy, through spacers and under-tray into rear sub frame and OEM captive nuts and tighten.
- Feed wiring up through under-tray as original.
- Connect wiring (suggest cutting OEM plug and using connectors supplied).
- Check all lights to ensure correct operation.
- Replace rear cowling.
- Replace seat
- Check all lights to ensure correct operation before use

R&G Racing

Unit 5K, Blacknest Industrial Park, Blacknest Road, Alton, Hampshire, GU34 4PX

Tel: +44 (0)870 220 6380 Fax: +44 (0)1420 521101 www.rg-racing.com Email: info@rg-racing.com



- **IMPORTANT: IF FITTING A FULL-SIZE LICENCE PLATE AND PLACING IT FAR DOWN ON THE LICENCE PLATE HANGER, THERE IS A SMALL CHANCE OF THE LICENCE PLATE HITTING THE BACK WHEEL UNDER HEAVY LOAD AND OVER LARGE BUMPS IN THE ROAD. IT IS YOUR RESPONSIBILITY TO CHECK FOR THIS POSSIBILITY AND TAKE AVOIDING ACTION. FAILURE TO CHECK THIS COULD RESULT IN SERIOUS INJURY.**

COUNTRY VERSION

- Remove seat.
- Remove rear cowling.
- Unplug OEM No plate and indicator wiring plug.
- Remove OEM tail-tidy (four screws underneath positioned horizontally and quick release pull cable under seat).
- Remove the two screws securing the under-tray to rear sub frame (positioned vertically under OEM tail-tidy).
- Fit OEM indicators (will need to cut loom) or r&g after market indicators (as pictured above) to new tail-tidy.
- Fit new No plate light as pictured above.
- Offer up new tail-tidy as above and secure using short button head screws and washers as shown and washers and nyloc nuts supplied in kit.
- Refit rear cowling (this is done now as it is used to secure tail-tidy)
- Position the two long spacers between front most holes in new tail-tidy and under-tray, on COUNTRY version fit the two M5 x 80mm long bolts with washers up through tail-tidy, through spacers, under-tray and into threaded clips on underside of seat cowling and tighten.
- Feed wiring up through under-tray as original.
- Connect wiring (suggest cutting OEM plug and using connectors supplied).
- Check all lights to ensure correct operation.
- Replace rear cowling.
- Replace seat
- Check all lights to ensure correct operation before use
- **IMPORTANT: IF FITTING A FULL-SIZE LICENCE PLATE AND PLACING IT FAR DOWN ON THE LICENCE PLATE HANGER, THERE IS A SMALL CHANCE OF THE LICENCE PLATE HITTING THE BACK WHEEL UNDER HEAVY LOAD AND OVER LARGE BUMPS IN THE ROAD. IT IS YOUR RESPONSIBILITY TO CHECK FOR THIS POSSIBILITY AND TAKE AVOIDING ACTION. FAILURE TO CHECK THIS COULD RESULT IN SERIOUS INJURY.**

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G Racing

Unit 5K, Blacknest Industrial Park, Blacknest Road, Alton, Hampshire, GU34 4PX

Tel: +44 (0)870 220 6380 Fax: +44 (0)1420 521101 www.rg-racing.com Email: info@rg-racing.com



R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in resellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.