



FITTING INSTRUCTIONS FOR CP0211BL CRASH PROTECTORS BUELL XB9-R, XB12-R & XB12-S '07 ONWARDS



Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – the rubber washers should be thrown away!

- Loosen both head bolts at front of engine.
- Remove one of the head bolts.
- Take the bar with the holes, one of the 7/16th UNC cap head bolts and 7/16th washer.
- Place washer over bolt and place bolt through the bar.
- Take one of the smaller spacers and place onto the bolt (largest diameter to the bar) and start bolt into engine mount. **DO NOT TIGHTEN YET!**
- Remove other mount bolt and repeat the same procedure.
- Tighten all bolts.
- Take one of the hex head bolts and one 10mm washer and slide up to head of bolt.
- Slide bolt through one of the crash protectors.
- Take one of the spacers, which slot through it and slide over bolt up to protector (slot facing away from protector).
- Screw assembly to one end of the bar.
- Tighten until you feel some compression from inside the protector. Continue to tighten until you feel the compression increase and resistance is met. Then make a quarter turn to nip it tight. Do not exceed 35nm - this can damage/weaken the components.
- Repeat for other side.

Due to the risk of cross threading of bolts etc; we always recommend that our products be fitted by one of our official dealers or a qualified mechanic.

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 5K, Blacknest Industrial Park, Blacknest Road, Alton, Hampshire, GU34 4PX

Tel: +44 (0)870 220 6380 Fax: +44 (0)1420 521101 www.rg-racing.com Email: info@rg-racing.com